

Specifikacije

4 TAKTNI											
Model/KS	30	25	18	15	9.8	8	6	5	4	3.5	2.5
Broj cilindara	3		2			1					
Snaga	30 KS (22.1 kw)	25 KS (18.4 kw)	18 KS (13.2 kw)	15 KS (11 kw)	9.8 KS (7.2 kw)	8 KS (5.9 kw)	6 KS (4.4 kw)	5 KS (3.7 kw)	4 KS (2.9 kw)	3.5 KS (2.6 kw)	2.5 KS (1.8 kw)
Obujam	526 cc (32.09 cu.in.)		328 cc (20.01 cu.in.)		209 cc (12.8 cu.in.)		123 cc (7.5 cu.in.)		85.5 cc (5.2 cu.in.)		
Provr i hod	61 x 60 mm (2.4 x 2.36 in.)		59 x 60 mm (2.32 x 2.36 in.)		55 x 44 mm (2.17 x 1.73 in)		59 x 45 mm (2.32 x 1.77 in)		55 x 36 mm (2.17 x 1.42 in)		
Upućivanje	Električno ili ručno						Ručno				
Komande	Ručica ili daljinske komande						Ručica				
Mjenjač	Naprijed - Neutral - Natrag										
Omjer prijenosa	1.92:1		2.15:1		2.08:1		2.15:1		2.15:1		
Dimenzije propelera	8" - 14"		6" - 10"		6.5" - 9.5"		7" - 9"		4.5" - 7"		
Visina krmenog zrcala	15",20"				15",20",25"		15",20"				
Gorivo	Bezolovni benzin (min 87 oktana)										
Ulje	SAE 10W-30/40 (SFSG,SH,SJ)										
Spremnik	25 L odvojeni spremnik		12 L odvojeni spremnik				1.1 L Integrirani spremnik ili 12 L odvojeni spremnik		1.1 L Integr. spremnik	1 L integr. spremnik	
Masa*	71.5 kg		52 kg		37 kg		25 kg		26 kg	17.5 kg	
Kapacitet punjenja baterije	12V 180W, 15A		Opcija: 12V 130W,11A		Opcija: 12V 80W,6A		Opcija: 12V 60W, 5A		N/A		
Maximalni režim (okr/min)	5,250-6,250	5,000-6,000	5,000-6,000				4,500-5,500		5,000-6,000	4,500-5,500	
Model/KS	30	25	18	15	9.8	8	6	5	4	3.5	2.5
Elektronsko ubrizgavanje goriva	S	S	—	—	—	—	—	—	—	—	—
Direktno ubrizgavanje	—	—	—	—	—	—	—	—	—	—	—
Elektronsko upućivanje CDI	S	S	S	S	S	S	S	S	S	S	S
Induktivni sistem upućivanja	—	—	—	—	—	—	—	—	—	—	—
Upućivanje sa zaštitom mjenjača	S	S	S	S	S	S	S	S	S	—	—
Termostatički kontroliran sistem hlađenja	S	S	S	S	S	S	S	S	S	S	S
Ispust kroz propeler	S	S	S	S	S	S	S	S	S	—	—
Vožnja u plitkim vodama	O	O	S	S	S	S	S	S	S	—	—
Alarm pritiska ulja	S	S	S	S	S	S	S	S	S	—	—
Power trim i tilt	O	O	—	—	—	—	—	—	—	—	—
Plinski amortizer tilta	O	O	—	—	—	—	—	—	—	—	—
Varijabilni minimum	—	—	—	—	—	—	—	—	—	—	—

LEGENDA S.....Standardno O.....Opcija